

PATENT APPLICATION

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re the Application of:

Lassi HIPPELÄINEN

Application No.: New Application

Filed: Concurrently Herewith

Attorney Dkt. No.: 60282.00155

For: IP ADDRESS MANAGEMENT

CLAIM FOR PRIORITY UNDER 35 USC § 119

Commissioner for Patents
P.O. Box 1450
Alexandria, VA 22313-1450

March 3, 2004

Sir:

The benefit of the filing dates of the following prior foreign application filed in the following foreign country is hereby requested for the above-identified patent application and the priority provided in 35 U.S.C. §119 is hereby claimed:

European Patent Application No. 03028897.1 filed on December 16, 2003 in Europe


In support of this claim, a certified copy of said original foreign application is filed herewith.

It is requested that the file of this application be marked to indicate that the requirements of 35 U.S.C. §119 have been fulfilled and that the Patent and Trademark Office kindly acknowledge receipt of this document.

THIS PAGE BLANK (USPTO)

Please charge any fee deficiency or credit any overpayment with respect to this paper to Counsel's Deposit Account No. 50-2222.

Respectfully submitted,

A handwritten signature in black ink, appearing to read 'Kevin F. Turner', written over a horizontal line.

Kevin F. Turner
Registration No. 43,437

Customer No. 32294
SQUIRE, SANDERS & DEMPSEY LLP
14TH Floor
8000 Towers Crescent Drive
Tysons Corner, Virginia 22182-2700
Telephone: 703-720-7800
Fax: 703-720-7802

KFT:lls

Enclosure: Priority Document

THIS PAGE BLANK (USPTO)



**Europäisches
Patentamt**

**European
Patent Office**

**Office européen
des brevets**

Bescheinigung

Certificate

Attestation

Die angehefteten Unterlagen stimmen mit der ursprünglich eingereichten Fassung der auf dem nächsten Blatt bezeichneten europäischen Patentanmeldung überein.

The attached documents are exact copies of the European patent application described on the following page, as originally filed.

Les documents fixés à cette attestation sont conformes à la version initialement déposée de la demande de brevet européen spécifiée à la page suivante.

Patentanmeldung Nr. Patent application No. Demande de brevet n°

03028897.1

Der Präsident des Europäischen Patentamts;
Im Auftrag

For the President of the European Patent Office

Le Président de l'Office européen des brevets
p.o.

R C van Dijk

THIS PAGE BLANK (USPTO)



Anmeldung Nr:
Application no.: 03028897.1
Demande no:

Anmeldetag:
Date of filing: 16.12.03
Date de dépôt:

Anmelder/Applicant(s)/Demandeur(s):

Nokia Corporation
Keilalahdentie 4
02150 Espoo
FINLANDE

Bezeichnung der Erfindung/Title of the invention/Titre de l'invention:
(Falls die Bezeichnung der Erfindung nicht angegeben ist, siehe Beschreibung.
If no title is shown please refer to the description.
Si aucun titre n'est indiqué se referer à la description.)

IP adress management

In Anspruch genommene Priorität(en) / Priority(ies) claimed /Priorité(s)
revendiquée(s)
Staat/Tag/Aktenzeichen/State/Date/File no./Pays/Date/Numéro de dépôt:

Internationale Patentklassifikation/International Patent Classification/
Classification internationale des brevets:

H04L29/12

Am Anmeldetag benannte Vertragsstaaten/Contracting states designated at date of
filing/Etats contractants désignées lors du dépôt:

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IT LU MC NL
PT RO SE SI SK TR LI

THIS PAGE BLANK (USPTO)

TBK-Patent POB 20 19 18 80019 München

EPO - Munich
20
16. Dez. 2003

Patentanwälte
Dipl.-Ing. Reinhard Kinne
Dipl.-Ing. Hans-Bernd Pellmann
Dipl.-Ing. Klaus Grams
Dipl.-Ing. Aurel Vollnhals
Dipl.-Ing. Thomas J.A. Leson
Dipl.-Ing. Dr. Georgi Chivarov
Dipl.-Ing. Matthias Grill
Dipl.-Ing. Alexander Kühn
Dipl.-Ing. Rainer Böckelen
Dipl.-Ing. Stefan Klingele
Dipl.-Chem. Stefan Bühling
Dipl.-Ing. Ronald Roth
Dipl.-Ing. Jürgen Faller
Dipl.-Ing. Hans-Ludwig Trösch
Rechtsanwälte
Michael Zöbisch

December 16, 2003
US 40184

NOKIA CORPORATION
Espoo, Finland

"IP ADDRESS MANAGEMENT"

Dresdner Bank, München Kto. 3939 844
Deutsche Bank, München Kto. 2861 060
Postbank, München Kto. 6704 3804
Mizuho Corp. Bank, Düsseldorf Kto. 810 423 3007
UFJ Bank Limited, Düsseldorf Kto. 500 047
Steuernr.: 9 148/641/28007 Ust-ID/VAT: DE 1307 480 35

BLZ 700 800 00
BLZ 700 700 24
BLZ 700 100 80
BLZ 300 207 00
BLZ 301 307 00

IBAN-Nr.: DE47 7008 0000 0393 9844 00
IBAN-Nr.: DE14 7007 0024 0286 1060 00
IBAN-Nr.: DE04 7001 0080 0067 0438 04
IBAN-Nr.: DE75 3002 0700 8104 2330 07
IBAN-Nr.: DE09 3013 0700 0000 5000 47

BIC: DRES DE FF 700
BIC: DEUT DE DB MUC
BIC: PBNK DE FF
BIC: MHCN DE DD
BIC: SANW DE DX

01Brief ohne Betreff_a.doc/1234567/MA317

EPO - Munich
20
16. Dez. 2003

TITLE OF THE INVENTION

IP Address Management

5 FIELD OF THE INVENTION

The present invention relates to an address management in networks in which addresses are allocated dynamically from a limited address pool. In particular, the invention relates to
10 managing addresses in an access network assigning addresses to users of an IP network.

BACKGROUND OF THE INVENTION

15 IP (Internet Protocol) addresses, such as IPv4 (IP version 4) addresses are a limited resource that has to be recycled: when a user loses a connection, the address will be assigned to a new user. In case the old user has disconnected brutally, i.e. a connection is lost without having a chance to inform
20 correspondent nodes about the connection loss, the address of the old user may have been reassigned to a new user before all of the old user's sessions have expired. As a result, the new user may receive packets that belong to the old user of the IPv4 address. For example, such connection losses are caused
25 by the old user moving out of a coverage area or running out of battery.

Although the new user has not asked for these packets, he has to pay for receiving them anyway. This "overbilling" attack
30 which happens e.g. in GPRS (General Packet Radio Service) and 3G (Third Generation) networks is a security incident.

Typically a stateful FW (FireWall) is used to stop incoming unsolicited packets. However, in the case of brutal disconnect
35 the FW states ("pinholes") are not reset, because the FW has

not been notified about the loss of the connection. Both TCP (Transport Control Protocol) and UDP (User Datagram Protocol) packets get through, if they match an old pinhole.

- 5 The time to wait until an address can be reassigned, i.e. a "cooling" time, varies, because there are no standard values for either TCP retry limit or UDP soft state lifetime. Typically TCP gives up only after several minutes of trying (depending on implementation), and UDP soft states live at
10 least one minute (depending on FW settings). Sessions can also end if a NAT (Network Address (and Port) Translator) along the path resets an address-port binding, because it has not been used for some predefined time. Details about NAT can be found in P. Srisuresh et al.: "Traditional IP Network Address
15 Translator (Traditional NAT)", Network Working Group, RFC 3022, January 2001. All of the above times can be different, and can be configured at different sites.

- For example, an address cooling mechanism using IPv6 is
20 described in applicant's WO 01/93540. However, previous suggestions of address cooling mechanisms have used only an estimate of the longest possible cooling period before an address can be reactivated, and used that to estimate the size of the required cooling queue. Such size may be uncomfortably
25 large for IPv4.

- Another suggestion is that the FW should read ICMP (Internet Control Message Protocol) error notifications transmitted to the senders, and close remaining pinholes to released
30 addresses as described in applicant's US 60/479509. More details about ICMP are described by J. Postel: "Internet Control Message Protocol", Network Working Group, RFC 792, September 1981.

Alternatively it has been suggested to use two FWs, one at Gn side of a GGSN (GPRS Gateway Serving Node) detecting PDP (Packet Data Protocol) context terminations, and another on the Gi side stopping packets to addresses that the first FW reports as unused. This solution is very expensive, because it requires installing FWs in many places. Also it is limited to GPRS and 3G networks.

Moreover, the FW suggestions may not help if a free address pool is small, and a new user happens to activate the same service that the old user had running. In this case the new user opens a pinhole that again lets the old user's session through.

15 SUMMARY OF THE INVENTION

It is an object of the invention to improve reassigning IP addresses to users in order to avoid extra packets for the users resulting e.g. in the overbilling attack.

According to an aspect of the invention, this object is achieved by a network device according to claim 1 and a method according to claim 14.

According to another aspect of the invention, the above object is achieved by a network device according to claim 9 and a method according to claim 15.

According to a further aspect of the invention, the above object is achieved by a system according to claim 13.

The invention may also be provided by a computer program product comprising software code portions to be executed by a computer, microprocessor or the like.

According to the invention, the size of a cooling queue will depend on averages, not maximum, because a cooling period of each address will adapt to stack implementations of correspondent nodes of an old user. Troublesome addresses
5 connected to long-living sessions may be sent back to the end of the cooling queue several times. With the invention the number of cooling addresses can be reduced significantly, because a free address pool needs only a few "cold" addresses that rise quickly to the front of the queue.

10

Furthermore, the solution according to the invention is independent of FW and NAT locations and timers.

15

Moreover, the cooling method of the invention can be extended to DHCP- (Dynamic Host Configuration Protocol) assigned addresses. Therefore the invention works with any access network.

20

In the following the present invention will be described by way of preferred embodiments thereof taking into account the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

25

Fig. 1 shows an address management according to the invention in case it is detected that a packet has been sent to a released address.

30

Fig. 2 shows an address management according to the invention in case it is detected that an address has been released.

Fig. 3 shows an address management according to the invention in case an address out of released addresses is to be reassigned.

35

Fig. 4 shows a schematic block diagram illustrating an address management entity according to an embodiment of the invention.

Fig. 5 shows a schematic block diagram illustrating an address management entity according to another embodiment of the invention.

DESCRIPTION OF THE INVENTION

10 Figs. 1, 2 and 3 show an address management scheme according to the invention. An address management entity shown in these figures is responsible for assigning addresses to IP network users and comprises a cooling queue 10 for holding released addresses such as released IPv4 addresses. An address release
15 may result from a connection loss which may be due to a brutal disconnect of a user.

The upper part of Fig. 1 shows the cooling queue 10 holding released addresses A1 to An. In case the address management
20 entity detects that a packet has been addressed to a released address held in the cooling queue 10, such as to the released address A4, the released address A4 is shifted to the end of the cooling queue 10. The result of this cooling queue update is shown in the lower part of Fig. 1. As shown in the lower
25 part of Fig. 1, the released addresses A5 to An have moved forward by one place to the front of the cooling queue 10 and the released address A4 is placed at the end of the cooling queue 10.

30 The upper part of Fig. 2 shows like the upper part of Fig. 1 the cooling queue 10 holding the released addresses A1 to An. In case the address management entity detects that an address of a user has been released, such as an address An+1, the released address An+1 is added to the end of the cooling

queue. The result of this cooling queue update is shown in the lower part of Fig. 2.

The upper part of Fig. 3 shows like the upper part of Figs. 1 and 2 the cooling queue 10 holding the released addresses A1 to An. In case an address out of the released addresses held in the cooling queue 10 is to be reassigned, e.g. because a free address pool is empty, the address at the beginning of the cooling queue is taken out as address to be reassigned. According to Fig. 3, since the address at the beginning of the cooling queue is the address A1, the address A1 is taken from the cooling queue 10 for reassigning. The result of this reassignment is shown in the lower part of Fig. 3.

As described above, the address management entity or Address Manager (AM) that is responsible for assigning addresses lets a released address "cool" until no packets to an old user having had the released address before are received. The cooling mechanism is adaptive: it uses the least-recently-used cooling queue 10. Released addresses go to the end of the cooling queue 10. In case e.g. a free address pool is empty, the first address in the cooling queue 10 (A1 according to Fig. 3) gets assigned to a next new user.

The idea is that each time an address already in the cooling queue 10 receives a packet, the address is returned to the end of the cooling queue 10. In addition, an error message (e.g. ICMP "not reachable") may be returned to a sender or source of the packet, e.g. a correspondent node of the old user, to inform it that sessions to the address are broken.

In case the address management entity is placed in a data path, like a GGSN, it can handle the queue internally. In other words, the address management entity may detect that a packet has been addressed to a released address held in the

cooling queue 10 by receiving a packet addressed to the released address. Furthermore, the address management entity may detect that an address of a user has been released by detecting a loss of a connection which releases its address.

5

Fig. 4 shows an embodiment of the invention in which the address management entity or address manager is in the data path, i.e., the address manager and an AR (Access Router) are integrated like in a GGSN that manages its own address pool.

10

In Fig. 4, the integrated address manager and access router block 30 is located in an access network, e.g. an IP based access network, providing access to an IP network for a user. The block 30 comprises the cooling queue 10.

15

In case the functions of the address management entity and those of the access router are combined as shown in Fig. 4, the loss of a connection releases its address, which is added to the end of the cooling queue 10 as shown in Fig 2. A next released address goes behind it, etc. But each time a packet arrives to a cooling address held in the cooling queue 10, the address is again returned to the end as shown in Fig. 1, and an ICMP error notification may be sent to the source of the packet by the integrated block 30.

20

25

Returning a released address repeats until all sessions that are bound to the released address have expired. After that the address can advance to the first position in the queue, and can then be assigned to a new user.

30

In case the address management entity and the data path are separated like e.g. in DHCP (Dynamic Host Configuration Protocol), an access router along the data path of the old user notifies the address management entity about lost connections, and also sends copies of error messages to the

35

address management entity, the error messages notifying

packets sent to unused addresses. The cooling queue is in the address management part. For details about DHCP it is referred to S. Alexander, R. Droms: "DHCP Options and BOOTP Vendor Extensions", Network Working Group, RFC 2132, March 1997.

5

In other words, in case the address management entity is not located in the data path of the old user, the address management entity may detect that a packet has been addressed to a released address held in the cooling queue 10 by

10

receiving an error notification indicating an unused address. Furthermore, the address management entity may detect that an address of a user has been released by receiving a notification thereon.

15

In case the access router in the data path receives a packet addressed to an unused address it sends an error notification to the address management entity, the error notification indicating the unused address. In addition, the access router may also send an error notification to a source of the packet.

20

Moreover, in case the access router detects a loss of a connection which releases its address, it sends a notification about the released and now unused address to the address management entity.

25

Fig. 5 shows a separated access router 42 and address management entity or address manager 41. The address manager 41 comprises the cooling queue 10. The access router 42 is located in the data path of the old user.

30

When the access router 42 loses a connection, it notifies the address manager 41 about the address that can be released. The address manager 41 puts the address in the cooling queue 10 as described above in connection with Fig. 2. If the access router 42 later receives a packet to an unused, i.e. released

35

address, it sends an error notification to the address manager

41, which pushes the address to the end of the cooling queue 10 as shown in Fig. 1. The access router 42 may also send an ICMP error as it is done in the integrated case above.

- 5 The message from the access router 42 to the address manager 41 to release an address can be RADIUS (Remote Authentication Dial-In User Service 'Accounting Stop'. The access router - address manager error notification protocol can be ICMP, but also a proprietary protocol is possible. Details about RADIUS
- 10 can be found in C. Rigney et al.: "Remote Authentication Dial In User Service (RADIUS)", Network Working Group, RFC 2865, June 2000, and C. Rigney: "RADIUS Accounting", Network Working Group, RFC 2866, June 2000.
- 15 The invention has been explained using a single LRU (Least Recently Used) cooling queue 10 per address range. However, it is possible to classify a released address into a group out of at least two address groups, each address group having its own cooling queue holding released addresses, and to add the
- 20 released address to the end of the queue of the classified group, the queues being given a priority order for re-assigning the released addresses held in the queues.

In other words, it is possible to classify the addresses as

25 being "troubled", or connected to misbehaving nodes, e.g. those that ignore ICMP errors. For example, an address may be classified as being troubled in case transmission attempts for this address continue in spite of an ICMP error report, or the number of packets sent to this address exceeds a configurable

30 limit. This classification may be carried out by the address management entity such as the integrated address manager and access router 30 or the address manager 41. Troubled addresses may be sent to a special queue by the address management entity which special queue is used for reassigning only when

35 the normal queue (i.e. the cooling queue 10) is empty.

Addresses in the queues given a higher priority than the special queue for "troubled" addresses will pass the troubled addresses. This way it is possible to avoid a situation where a non-cooled address gets reassigned, because it has not been
5 accessed for some time, and during that time it has reached the front of the cooling queue 10.

It is to be understood that the above description is illustrative of the invention and is not to be construed as
10 limiting the invention. Various modifications and applications may occur to those skilled in the art without departing from the true spirit and scope of the invention as defined by the appended claims.

15

EPO - Munich
20
16. Dez. 2003

CLAIMS:

1. A network device for managing addresses to be assigned to users of an IP network, the network node comprising:

- 5 at least one queue for holding released addresses,
 the network device being arranged to:
 detect that a packet has been addressed to a released
address held in the at least one queue; and
 return the held address to which the packet has been
10 addressed to the end of the at least one queue.

2. The network device according to claim 1, further being arranged to:

- detect that an address of a user has been released; and
15 add the released address to the end of the at least one
queue.

3. The network device according to claim 2, further being arranged to:

- 20 classify the released address into a group out of at least
two address groups, each address group having its own queue
holding released addresses; and
 add the released address to the end of the queue of the
classified group, the queues being given a priority order for
25 re-assigning the released addresses held in the queues.

4. The network device according to any one of claims 1 to 3, further being arranged to:

- upon detection that a packet has been addressed to a
30 released address held in the at least one queue, send an error
notification to a source of the packet.

5. The network device according to any one of claims 1 to 4,
wherein the network device is arranged to detect that a packet
35 has been addressed to a released address held in the at least

one queue by receiving a packet addressed to the released address.

6. The network device according to any one of claims 2 to 5, wherein the network device is arranged to detect that an address of a user has been released by detecting a loss of a connection which releases its address.

7. The network device according to any one of claims 1 to 3, wherein the network device is arranged to detect that a packet has been addressed to a released address held in the at least one queue by receiving an error notification indicating an unused address.

8. The network device according to claims 2, 3 or 7, wherein the network device is arranged to detect that an address of a user has been released by receiving a notification thereon.

9. A network device for forwarding IP data packets, the network device being arranged to:

receive a packet addressed to an unused address; and
send an error notification to a network node for managing addresses, the error notification indicating the unused address.

10. The network device according to claim 9, wherein the error notification causes returning a released address held in a queue and corresponding to the unused address to the end of the queue, the queue holding released addresses.

11. The network device according to claim 9 or 10, further being arranged to:

detect a loss of a connection which releases its address;
and

send a notification about the released address to the network node for managing addresses.

12. The network device according to any one of claims 9 to 11,
5 further being arranged to:

upon receipt of the packet addressed to the unused address, send an error notification to a source of the packet.

13. A system for managing addresses to be assigned to users of
10 an IP network, comprising:

a network node for managing addresses according to any one of claims 1 to 3, 7 and 8; and

a network node for forwarding IP data packets according to any one of claims 9 to 12.

15

14. A method of managing addresses to be assigned to users of an IP network, the method comprising the steps of:

detecting that a packet has been addressed to a released address held in a queue holding released addresses; and

20 returning the held address to which the packet has been addressed to the end of the queue.

15. A method of forwarding IP data packets, the method comprising the steps of:

25 receiving a packet addressed to an unused address; and
sending an error notification to a network node for managing addresses, the error notification indicating the unused address.

30 16. The method according to claim 15, wherein the error notification causes returning a released address held in a queue and corresponding to the unused address to the end of the queue, the queue holding released addresses.

17. A computer program product comprising software code portions for performing the steps of any one of claims 14 to 16, when said product is run on an computer.

5 18. The computer program product according to claim 17, further comprising a computer-readable medium on which the software code portions are stored.

10 19. The computer program product according to claim 17, wherein the computer program product is directly loadable into an internal memory of the computer.

16. Dez. 2003

ABSTRACT:

Managing addresses to be assigned to users of an IP network is described, in which it is detected that a packet has been
5 addressed to a released address held in a queue for holding released addresses, and the held address to which the packet has been addressed is returned to the end of the queue.

(Fig. 1)

THIS PAGE BLANK (USPTO)




Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5

THIS PAGE BLANK (USPTO)